

Product Specifications

Product: Meter/Pit Insulation Plug

Product Characteristics

Plug Body: 1.2# laminated closed cell polyethylene foam, USA origination
R-value 2.6 per inch
MP4 Pit Plugs have a minimum height of 4"
MP6 Pit Plugs have a minimum height of 6"
Sediment and water resistant

Handle: 3/8" Hollow Braid Polypropylene, USA origination
Tensile strength: 1800 lbs., safe working load: 306 lbs.

Handle connection: Long bury spliced with 2 heat welds. The handle is installed through the body of the plug and heat welded. The polypropylene handle is highly visible and is resistant to rot, mildew, oils, gas and most chemicals.

Pit Plugs	Unit Weight (lb)	Description
MP-15	.50	15" x 4" Pit Plug
MP6-15	.80	15" x 6" Pit Plug
MP-18	.70	18" x 4" Pit Plug
MP6-18	1.10	18" x 6" Pit Plug
MP-21	.90	21" x 4" Pit Plug
MP6-21	1.40	21" x 6" Pit Plug
MP-24	1.20	24" x 4" Pit Plug
MP6-24	1.90	24" x 6" Pit Plug
MP-36		36"x36-1/4"x4" Plug
Call for custom cut plugs up to 48"		



*ID of pipe is needed for the best fit.

This product is made in the USA.



Made in USA
www.ckrproducts.com
SARTELL, MN 56377 USA