

# Product Specifications

**Product:** Manhole Rehab Plug

## Product Characteristics

**Plug Body:** 1.7# laminated closed cell polyethylene foam/ 4" MDL, USA origination  
R-value 2.5 per inch  
Minimum height of 4"  
Sediment and water resistant

**Handles:** 3/8" Hollow Braid Polypropylene  
Tensile strength: 1800 lbs., safe working load: 306 lbs.  
Inside handles to adjust the fit into a casting.  
Outside handles to easily remove the plug.

**Handle connection:** Long bury spliced with heat welds. The handles are installed through the body of the plug and heat welded. The polypropylene handles are highly visible and resistant to rot, mildew, oils, gas and most chemicals.

| Product # | Unit Weight (lb) | Description         |
|-----------|------------------|---------------------|
| MRP-24    | 2.12             | 24" x 4" Rehab Plug |
| MRP-27    | 2.65             | 27" x 4" Rehab Plug |
| MRP-30    | 3.30             | 30" x 4" Rehab Plug |
| MRP-32    | 3.70             | 32" x 4" Rehab Plug |
| MRP-34    | 4.20             | 34" x 4" Rehab Plug |
| MRP-36    | 4.65             | 36" x 4" Rehab Plug |



Scan QR code for installation demonstration.



Made in USA

[www.ckrproducts.com](http://www.ckrproducts.com)

SARTELL, MN 56377 USA